

# SD7 / SD7 PLUS

SD7



**Operation:** A reliable all-metal mortise lock for sliding doors having a latch bolt that is retracted by operation of either an outside or inside lever. Once latched it may be locked (or unlocked) from either side by key.

### **Special Features:**

- **Self-latching lock bolt** engages automatically when the door is closed.
- **Anti-lift pin** on catch plate engages the lock body to prevent the sliding door being lifted out of its tracks.
- Interior snib locking feature.
- Australian design and manufacture.
- Subject to patenting.

## 'SD7 Plus' Additional Features:

The SD7 Plus employs a steel catch plate and steel beak to provide additional jemmy resistance.

**Multipoint:** SD7 may be connected to multipoint kits to provide three point locking. These kits provide a top and a bottom locking beak, each connected to the main lock body by a steel cable or rod. The remote beaks are activated whenever the door is locked by key or snib (see over page for details).

# **SD7 PLUS**



SD7 Plus has a steel catch plate and steel beak.


### **Installation Features:**


- Fits into industry standard cut-outs.
- Standard lock fits door frames from 19mm to 21mm thick.
- Optional 'Fat Pack' allows fitting into doors 35mm to 40mm thick.
- Suits both left hand closing and right hand closing doors.
- Fitting instructions can be downloaded from www.ausloc.com

**Finishes:** A range of powder coated finishes shown in Section 10 of this catalogue. Finishes include PSIL (powder-coated Satin Chrome look-alike).

**Keying:** - AA 5-pin double cylinders

- C4 or Gainsborough compatible keyways
- can be keyed alike





Ordering Code	Description	Notes
SD7 / colour	SD7 standard	
SD7PLUS / colour	SD7 with steel beak and steel strike	
SD7NC / BLST	SD7 with No Cylinder hole	available in black only

see accessories page for further options.



# **Multipoint Kits**

# SD14Plus

### **Cable System**

Uses steel cables that provide quiet and reliable operation. Cables are available in three standard lengths.



## S14R **Rod System** Uses simple steel rods that are available in three standard lengths.



S14R-A				
Adjustable Rod Uses steel rods that can be set to any length and fixed with a special brass coupling.				

65	
172 156	25 [A] 60 19 60
65	16 Slot Width

	Ordering Code	Description	[A]	[B]
щ	SD14Plus/H	Cable operated multipoint kit for SD7 series	546mm	961mm
혈	SD14Plus/L	Cable operated multipoint kit for SD7 series	961mm	546mm
ડ	SD14Plus/P	Cable operated multipoint kit for SD7 series	375mm	961mm
	S14R/H	Rod operated multipoint kit for SD7 series	546mm	961mm
2	S14R/L	Rod operated multipoint kit for SD7 series	961mm	546mm
8	S14R/P	Rod operated multipoint kit for SD7 series	375mm	961mm
	S14R/A	Adjustable Rod multipoint kit for SD7 series	any	any

Tolerance +/- 3 mm

# **Accessories**

# AA-C4/ KA or KD

#### AA-G/ KA or KD

AA re-pinable double cylinder with C4 or Gainsborough compatible keyway.



# AA-C4LHTT/ KA or KD

#### AA-C4RHTT/ KA or KD

AA cylinder with Thumbturn on inside and 5-pin C4 outside. (refer Cylinder section for details)



# W2000/ KA

W2000 double wafer cylinder.



SD7-FP


SD7 'Fat Pack' to fit doors 35mm-40mm thick

#### Pack contains:

- 2 x lever coupling
- 1 x long snib lever (left)
- 1 x long snib lever (right)
- 2 x G8-32x2" CSK SS screws


# SD-TS KIT

Kit containing a thin strike plate (4mm) for SD7 locks.




#### SD-EX KIT

Kit containing SD7 levers with longer square drive (11mm) for use with wider doors.



#### SP6

Standard SD7 strike plate.



### SD7LH / colour **SD7 Long Handles**

SD7 lock body with Elegance levers for use on internal doors.

Snib locking only. Ideal for sliding partitions.



# SD-AL KIT


Kit containing a narrow strike and lever coupling to offset an SD7 lock.






# SD-NZ KIT

Kit containing a strike plate for NZ frames with central rib.



### SP9 Standard strike

plate for SD14 and S14R.



# **Sliding Security Door Products**